

## HKS twinface 16 mm, oak

Type/Construction	plankwood flooring, approx. 6 mm top layer, based on finger-jointed solid oak
Dimensions	16/6 x 180 mm
Lengths	random lengths 600 - 2.000 / 2.200 / 2.400 / 2.600 / 2.800 mm; 6 layer per box (2-2-0)
Packaging	shrinking foil, maintenance and installing instructions included
Profile	tongue and groove all around, 4 sides bevel (GO4)
Finishes	light brushed + natural oiled (Osmo hardwax) / sanded + invisible-look oiled (Osmo hardwax)
Production	according to EN 13489
Grading*	<b>ABCD</b> - according to the quality description of the manufacturer. To be expected: sound knots, filled knots, smaller cracks, filled cracks in the surface, rarely cracks in the filler, vivid structure, natural differences in colour, sapwood up to ¼ of the width, other wood typical marks.
Installation	glueing down on concrete or floating installation on Elastilon strong
Maintenance	depending on wear and tear, use with suitable maintenance products
Underfloor heating	suitable for warm water system only, no electric heating systems, surface temperature max. 29° C with equal heating, heat conductivity 0,17 W (m k); thermal resistance 0,094 m² K/W
Fire resistance	Cfl-s1
Labelling	CE
Hints	Wooden floorings are a natural product, due to climate conditions joints can occur in winter and the planks can swell in summer. Therefore an expansion gap to the walls of min. 15 mm is necessary. According to the behaviour of the planks the customer must be advised.



\*According to the factory standard, 3% clause to EN standard, max. 3% of the complete delivery including the cutting differences can differ from the grading description. The material must be checked before installation, claims after the installation are impossible.